



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MC146GY

Description Stranded 21 AWG (7/0.2mm) PACW, 6Cores, PVC Insulation, PVC Sheath.

AS/CA S-008, BS4737-3.30, AS 1049 Applicable Standards

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as


Suitable Applications intercommunication.

Not suitable for mains connection.

Cable Construction Drawing

Cable Construction Relative Parts









	Cable Description					
	Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
		21	14/0.2	0.44	0.87	PACW
	Insulation	Cores: 6 Material: PVC Colour: White, Blue, Red, Black, Yellow, Green Nominal Thickness (mm): 0.3 Nominal OD (mm): 1.5				
	Sheath	Material : Colour : Nominal Thickness (mm) Nominal OD (mm) :		PVC Grey (RAL 70 n): 0.65 6.1	046)	

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Electrical	Properties						
Voltage Rat	ing	ELV					
Max. Condu	Max. Conductor DC Resistance @ 20°C		45.2 Ω /km				
Min. Insulat	ion Resistance @ 20°	°C 50MΩ.l	50MΩ.km 1.5 kV ac/1min				
Voltage Tes	t: Conductor to core	1.5 kV					
Voltage Test: Core to sheath			3.0 kV ac/1min				
Mechanic	cal Properties						
Operating T	emperature Range	-15 to	70 ℃				
Max. Recommended Pulling Tension Min. Bend Radius (install)		sion 166N					
		61mm	61mm				
Approximate Mass			5.47kg/100m				
Sheath Printing			GARLAND SECURITY CABLE MC146 - 6 x 14/0.2 22AWG - MM/YYYY - "Mmark"				
Supply Ir	nformation						
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet			
100m	Plastic Reel	10 x 4.5 x 4.5"	4R				

Document Change Record	Issue	Date	Prepared by	Approved By
	01	24-11-2012	LLS	Pent
Changa History	Issue	Change		
Change History				

With Garland, you are always well connected.

