

Security Cable



Part No: MC146-W

Description Stranded 21AWG PACW, 6 Cores, PVC Insulation, PVC Sheath.

Applicable Standards AS/CA S-008, BS4737-3.30, AS 1049

Suitable Applications For inter-connecting wiring, suitable for use in Security/Intruded Alarm system; Use in low voltage/low current applications such as intercommunication.

Not suitable for mains connection.

Images




Image for illustration purposes only.



Construction

Conductor	Material	PACW
	No. of Strands	14
	Strand Size	0.2 mm
Insulation	Cores	6
	Material	V-75 PVC
	Colour	White, Blue, Red, Black, Yellow, Green
	Nominal Thickness (mm)	0.4
	Nominal Diameter (mm)	1.5
Sheath	Material	4V-75 PVC
	Colour	Refer to Packing Table
	Nominal Diameter (mm)	6.1
	Nominal Thickness (mm)	0.6

Garland's Work Series range is the experts' choice for high quality cables.

MC146-W210427

Security Cable



Properties	Voltage Rating	ELV
	Operating Temperature Range	-15 to 7°C
	Max. Recommended Pulling Tension	160N
	Min. Bend Radius (install)	60 mm
	Approximate Mass	5.5kg/100 m

Supply Information	Part Number	Pack Size	Jacket Colour	Carton/Box size (cm)	Carton/Reels	Boxes x Reels Per Pallet
	MC146WH100W	100m	White	46 x 24 x 15.5	4	24 x 4
	MC146WH250BW	250m	White	36 x 36 x 21	-	36
	MC146BK250BW	250m	Black	36 x 36 x 21	-	36

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

Garland's **Work Series** range is the experts' choice for high quality cables.