



Network

Multi-sensor

PNM-9000QB

2MP x 4CH Remote Head Camera



Key Features

- 2MP x 4CH
- HDMI - Single/Quad view support
- WDR 120dB, WiseStreamII
- Defocus detection, directional detection, motion detection etc
- Max 30fps@2MP
- H.265, H.264, MJPEG

Compatible Accessories (Optional)



SBL-100D

PNM-9000QB

2MP x 4CH Remote Head Camera



Specifications

Video	
Resolution	1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264: 2MP Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps/25fps(60Hz/50Hz)
Video Out	HDMI(1920x1080, Single/Quad view)
Lens	
Optional Lens	SLA-T1080FA, SLA-T2480A, SLA-T2480VA, SLA-T4680A, SLA-T4680VA
Operational	
Camera Title	Displayed up to 85 characters
Day & Night	Auto(Electrical)
Backlight Compensation	BLC, HLC, WDR, SSSDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR V
Digital Image Stabilization	Support
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	32ea, 4point quadrangle zones - Color: Grey/Green/Red/Blue/Black/White - Mosaic
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC	Support
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2~1/12,000sec)
Video Rotation	Flip, Mirror
Analytics	Defocus detection, Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line
Alarm I/O	Input 2ea / Output 2ea
Alarm Triggers	Analytics, Network disconnect, Alarm input
Alarm Events	File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC at event triggers Alarm output
Audio In	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
Audio Out	Line out, Max.output level: 1Vrms
Network	
Ethernet	RJ-45(10/100/1000BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High, MJPEG

Audio Compression	G.711 u-law /G.726 Selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps AAC-LC: 48Kbps at 16KHz
Smart Codec	Manual(5ea area), WiseStream II
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 12 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) Device Certificate(Hanwha Techwin Root CA)
Application Programming Interface	ONVIF Profile S/T SUNAPI(HTTP API)
General	
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Edge Storage	Micro SD/SDHC/SDXC 2slot 1TB(512GB X 2)
Memory	4GB RAM, 512MB Flash
Environmental & Electrical	
Operating Temperature / Humidity	-10°C ~ +45°C(14°F ~ +113°F) / Less than 95% RH(Non condensing)
Storage Temperature / Humidity	-50°C ~ +60°C(-58°F ~ +140°F) / Less than 90% RH
Input Voltage	PoE+(IEEE802.3at, Class4), 12VDC
Power Consumption	PoE : Max 22.00W, Typical 16.70W DC : Max 19.00W, Typical : 14.00W
Mechanical	
Color / Material	White / Plastic
RAL Code	RAL9003
Product Dimensions / Weight	200(W)x37(H)x146(D)mm / 715g

Compatible lenses



	SLA-T4680VA	SLA-T2480A	SLA-T4680A	SLA-T2480VA	SLA-T1080FA
Video	SLA-T4680VA	SLA-T2480A	SLA-T4680A	SLA-T2480VA	SLA-T1080FA
Imaging Device	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS
Effective Pixels					
Min. Illumination	Color: 0.06Lux(F2.5, 1/30sec)	Color: 0.045Lux(F2.0, 1/30sec)	Color: 0.06Lux(F2.5, 1/30sec)	Color: 0.045Lux(F2.0, 1/30sec)	Color: 0.03Lux(F1.6, 1/30sec)
Lens	SLA-T4680VA	SLA-T2480A	SLA-T4680A	SLA-T2480VA	SLA-T1080FA
Focal Length (Zoom Ratio)	4.6mm fixed focal	2.4mm fixed focal	4.6mm fixed focal	2.4mm fixed focal	1.6mm fixed focal
Max. Aperture Ratio	F2.5	F2.0	F2.5	F2.0	F1.6
Angular Field of View	H: 73°, V: 39°, D: 85°	H: 138°, V: 73°, D: 165°	H: 73°, V: 39°, D: 85°	H: 138°, V: 73°, D: 165°	H: 187°, V: 113.9°
Lens Type					
Mount Type	RJ12 connected with main unit	RJ12 connected with main unit	RJ12 connected with main unit	RJ12 connected with main unit	RJ12 connected with main unit
Focus Control	fixed	fixed	fixed	fixed	fixed
Pan / Tilt / Rotate	SLA-T4680VA	SLA-T2480A	SLA-T4680A	SLA-T2480VA	SLA-T1080FA
Pan / Tilt / Rotate Range					
Operational	SLA-T4680VA	SLA-T2480A	SLA-T4680A	SLA-T2480VA	SLA-T1080FA
Wide Dynamic Range					
Day & Night					
Mechanical	SLA-T4680VA	SLA-T2480A	SLA-T4680A	SLA-T2480VA	SLA-T1080FA
Color / Material	Black / Plastic, Metal	Black / Plastic	Black / Plastic	Black / Plastic, Metal	Black / Metal
Product dimensions / weight	W30xH27.9xD45mm, 321g	Ø24xL49.8mm, 318g	Ø24xL49.8mm, 310g	W30xH27.9xD45mm, 328g	Ø35xL68.9mm, 430g